DAV PUBLIC SCHOOL, AURI

P.O.-ANPARA, DISTT-SONEBHADRA – 231225(U.P.)

Notice Inviting Tender

Sealed bids for "Construction for DAV School Auri, P.O.- Anpara, Pargana – Singrauli, Tehsil-Duddhi, Distt-Sonebhadra (U.P.) are invited from all eligible & interested contractor / Firm having relevant experience of carrying out similar works.

interested contractor / I fill having relevant experience of earlying out similar works.							
Name of Work	Construction work for DAV School Auri, P.O. – Anpara,						
	Pargana – Singrauli, Tehsil- Duddhi, Distt- Sonebhadra						
	(U.P.) including Main Gate, Guard room & Boundary Wall,						
	Building Elevation work and other as mentioned in detail						
	tender document.						
Estimated cost of	42,05,086.00/-						
project	(In words: Forty-Two Lakhs Five Thousand Eighty-six						
	only)						
EMD Earnest Money	85,000/-						
	(In words: Eighty-Five thousand only)						
Tender Participation	3,000/-						
Fees (Non-Refundable)	(In words: Three thousand only)						
Project Completion	03 Months						
Period							
Last Date of	13.07.2024 by 4.00 P.M.						
Submission of Tender							
Date of Opening of	15.07.2024 by 3.00 P.M.						
Tender							

General Terms & Conditions: -

- 1. Blank Bidding document can be downloaded from DAV Public School, Auri. Website i.e. www.davpsauri.org, www.davpsrbts.org.
- 2. The Tender Document shall be submitted in sealed envelope duly at Technical and price bid for Tender for construction of specified work at DAV Public School, Auri.
- 3. Completely filled and duly Sealed Technical Financial proposal should be delivered along with separate envelope carrying EMD amount & Tender Participation Fees in Separate two Demands Draft payable to RRJS DAV Public School A Unit of DAYANAND, Canara Bank ,Anapara, Uttar Pradesh Pin- 231225 to be sent to The ARO,DAV Institutions UP Zone-D, C/O DAV Sr. Sec. Public School, Churk Road Robertsganj, P.O.-Robertsganj, Distt- Sonebhadra (U.P.)-231216 by the way of Speed Post or by Hand on or before 13.07.2024, 4;00 pm.
- 4. Financial Bids proposal of only technically qualified bidders will be opened on 15.07.2024 in presence of bidders or their representative.
- 5. The Committee of DAV Public School Reserves the rights to accept or reject all or any bid / Proposal without assigning any reason whatsoever.
- 6. For any Tender related query, the participants can contact: Mr. Nitish Srivastav-+91-8423522313.

BILL OF QUANTITY (ENTRANCE GATE)

NAME OF WORK -PROPOSED ESTIMATE FOR ENTRANCE GATE OF D.A.V. PUBLIC SCHOOL BUILDING , AURI ON GATA NO.-944 DA & 944 GHA AT POST-ANPARA, PARGANA-SINGRAULI, TEHSIL-DUDDHI, DISTRICT:-SONEBHADRA.

S.N.	DESCRIPTION OF ITEM	SCHEDULE REF. NO.	QUANTITY	UNIT	RATES	Amount
1	Earth work in exacavation in foundation in ordinary soil including lift upto 1.5 m and lead upto 30m. and dressing of sides and ramming of bottom and disposal of surplus excavated earth as directed by the Engineer i/c with in a lead of 30 m.					
	Filling with avilable earth in trenches, plinth, sides of foundation, etc.in	PWD-251	68.28	CUM		
2	layers not exceeding 20 cms in depth consolidating each deposited layer by ramming and watering including lead upto 50m and lift upto 1.5m.	PWD-255	47.80	CUM		
2	Providing and laying in cement concrete 1:4:8 (1 cement : 4 coarse sand : 8 graded brick aggregate 20 mm nominal size) and curing complete, including cost of form-work, in foundation and floors.	PWD 281	14.27	CUM		
4	Providing and injecting chemical emulsion for pre-constructional antitermite treatment and creating a chemical barrier under and alround the column pits wall trenches basement excavation top surface if plinth filling junction surrounding of pipe sand conduits etc, complete (plinth area of the building at ground floor only shall be measured as per I.S.6313 (Part-II-1981) Alderine emulsifiable concentrate or any other approved material such as Heptrachlor or chordance will be used. The rate of application of chemical emulsion shall be as follows:					
	(1)Treatment for masonary & foundation 5 liters per/100 sqm.					
	(2) Back fill in immediate contact with foundation 7.5 liters/100sqm					
	(3) Treatment of top surface of plinth filling 5 liters/100 sqm (4)Treatment junction of wall and the floor 7.5 liters /100 sqm					
	(5)Treatment of soil along external perimeter of building 7.5 liters/100sqm.					
	(6) Treatment of soil under apron along external perimter 5 liters/100 sqm.	PWD par2018	25.65	SQM		
5	R.C.C. work with cement approved coarse sand and 2 cm (3/4") gauge approved stone ballast in the proportion 1:1.5:3 (1 cement :1.5 coarse sand : 3 aggregates) , in raft foundation and footings excluding supply of reinforcement and its bending the same with 24 WG binding wire and necessary centring and shuttering etc and also including supply of all materials labour and tools and plants etc. required for proper completion of the works.	PWD 287+(289- 288)	17.47	CUM		
6	R.C.C. work with cement approved coarse sand and 2 cm (3/4") gauge approved stone ballast in the proportion 1:1.5:3 (1 cement :1.5 coarse sand : 3 aggregates) , in lintels of doors and windows excluding supply of reinforcement and its bending the same with 24 WG binding wire and necessary centring and shuttering etc and also including supply of all materials labour and tools and plants etc. required for proper completion of the works.	PWD 283+(289- 288)				
		,	0.26	CUM		
7	As in item 8.0 above but in lighter Beams having spans upto above six meter	PWD 285				
8	As in item 8.0 above but in SLAB	PWD 284	8.92	CUM		
9	R.C.C. work with cement approved coarse sand and 2 cm (3/4") gauge approved stone ballast in the proportion 1:1.5:3 (1 cement :1. coarse sand : 2 aggregates), columns excluding supply of rienforcement and its bending the same with 24 WG binding wire and necessary centring and shuttering etc and also including supply of all materials labour and		12.47	CUM		
	tools and plants etc. required for proper completion of the works. GROUND FLOOR TO TOP	PWD 289	4.97	CUM		
10	Mild steel or iron in plain work such as reinforced concrete or reinforced, brick work (when not included in an over all rates) wrought to required shape as necessary including bending for proper completion of the work and including supply of steel its wastage bend hooks and authorised over lapping shall be measured upto floor two level.					
	First Class brick work in 1:6 cement and fine sand of mortar in	PWD 504	39.09	QTL		
11	foundation and plinth including and plinth including supply of all materials labour and T&P etc. required for proper complete of the work.	PWD 303+(307-				
		306)	4.55	CUM		

BILL OF QUANTITY (ENTRANCE GATE)

NAME OF WORK -PROPOSED ESTIMATE FOR ENTRANCE GATE OF D.A.V. PUBLIC SCHOOL BUILDING , AURI ON GATA NO.-944 DA & 944 GHA AT POST-ANPARA, PARGANA-SINGRAULI, TEHSIL-DUDDHI, DISTRICT:-SONEBHADRA.

S.N.	DESCRIPTION OF ITEM	SCHEDULE REF. NO.	QUANTITY	UNIT	RATES	Amount
12	Same as in item no. 15 above but in super-structure including necessary cutting and moulding of brick work as required and also including honey combed brick work in thickness of wall one brick thick. 1:6 1 cement and 6 coarse sand mortar					
	GROUND FLOOR TO TOP	PWD 303+309+310	43.47	CUM		
13	External Plastering 12 mm thick plaster with cement mortar in proportion of 1:6cement & fine sand of along for external walls	PWD 586	101.70	SQM		
14	Internal Plastering 12mm thick plaster with cement mortar in proportion of 1:4 cement & coarse sand of along for internal walls	PWD-584	101.70	SQM		
15	Kota stone slab flooring over 20 mm (average) thick base of cement mortar 1:4 (1 cement:4 coarse sand)laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete with:					
	(a) 25 mm thick	DSR 11.26	18.000	SQM		
16	2.5 cm thick 1:2:4 plain cement concrete floor with cement approved coarse sand 2cm graded approved stone laid in panels finished with 3 mm in 5:1 as specifiled over & including 8cm thick base concrete conisting of cement local sand and brick ballast 4cm gauge in the proportion of 1:4:8 and removing any over lapping mortar at the joints of panels if any and giving them a uniform finish including supply of all materials labour and T&P etc. required for proper completion of the work.					
	As item no 20 above but floors shall be 4cm thick instead of 2.5 cm thick and without base concrete.	PWD 605	18.00	SQM		
17	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade: New work (two or more coats) over and including water tinnable priming coat with cement primer	PWD 649+650	101.70	SQM		
18	Finishing walls with Acrylic smmoth exterior paint of required shade : New work (Two or more coats applied @ 1.67 ltr/10 sqm) over and including priming coat of exterior primer applied @ 2.20kg/ 10 sqm	PWD CH.15 SN22	101.70	SQM		
19	Providing & applying Birla putty of Av. 1. mm thickness over plastered surface to prepare the surface even & smooth complete	PWD CH.15 SN30	203.40	SQM		
20	Supply & fixing of M.S Gate of 6 meter wide, as per the design, & drawing.	M.R	2.00	Nos.		
21	Exterior landscape work & Lighting provision on gate as per direction & drawing of engineer- in charge.	L.S	1.00	Nos.		
22	Supply & fixing of z section Door frame with m.s door as per design & drawing.	L.S	2.00	Nos.		
23	Supply & fixing of UPVC WINDOW	L.S	2.00	Nos.		
24	Elevation façade treatment including light arrangement , Painting, fixed Glazing along with M.s Hollow Pipe as per direction of engineer-incharge.	L.S	1.00	Nos.		
	TOTAL ESTIMATED COST					
	Contengency 5% of estimated Cost					
	TOTAL ESTIMATED COST					

BILL OF QUANTITY (Boundary wall)

ON GATA NO.-944 DA & 944 GHA AT POST-ANPARA, PARGANA-SINGRAULI, TEHSIL-DUDDHI, DISTRICT:SONEBHADRA.

S.N.	DESCRIPTION OF ITEM	SCHEDULE REF. NO.	Qty	UNIT	Rates	Amount
1	Earth work in exacavation in foundation in ordinary soil including lift upto 1.5 m and lead upto 30m. and dressing of sides and ramming of bottom and disposal of surplus excavated earth as directed by the Engineer i/c with in a lead of 30 m.		4.75	CUM		
2	Filling with avilable earth in trenches, plinth, sides of foundation, etc.in layers not exceeding 20 cms in depth consolidating each deposited layer by ramming and watering including lead upto 50m and lift upto 1.5m.		3.33	CUM		
2	Providing and laying in cement concrete 1:4:8 (1 cement : 4 coarse sand : 8 graded brick aggregate 20 mm nominal size) and curing complete, including cost of form-work, in foundation and floors.		0.36	CUM		
5	R.C.C. work with cement approved coarse sand and 2 cm (3/4") gauge approved stone ballast in the proportion 1:1.5:3 (1 cement :1.5 coarse sand : 3 aggregates) , in raft foundation and footings excluding supply of reinforcement and its bending the same with 24 WG binding wire and necessary centring and shuttering etc and also including supply of all materials labour and tools and plants etc. required for proper completion of the works.		0.66	CUM		
6	R.C.C. work with cement approved coarse sand and 2 cm (3/4") gauge approved stone ballast in the proportion 1:1.5:3 (1 cement :1.5 coarse sand : 3 aggregates) , in lintels of doors and windows excluding supply of reinforcement and its bending the same with 24 WG binding wire and necessary centring and shuttering etc and also including supply of all materials labour and tools and plants etc. required for proper completion of the works.					
	plinth beam		0.21	CUM		
9	R.C.C. work with cement approved coarse sand and 2 cm (3/4") gauge approved stone ballast in the proportion 1:1.5:3 (1 cement :1. coarse sand : 2 aggregates) , columns excluding supply of rienforcement and its bending the same with 24 WG binding wire and necessary centring and shuttering etc and also including supply of all materials labour and tools and plants etc. required for proper completion of the works.					

	BOUNDARY WALL		0.37	CUM		
10	Mild steel or iron in plain work such as reinforced concrete or reinforced, brick work (when not included in an over all rates) wrought to required shape as necessary including bending for proper completion of the work and including supply of steel its wastage bend hooks and authorised over lapping shall be measured upto floor two level.	PWD 504	1.05	QTL		
11	First Class brick work in 1:6 cement and fine sand of mortar in foudation and plinth including and plinth including supply of all materials ,labour and T&P etc. required for proper complete of the work.	PWD	0.47	CUM		
12	Same as in item no. 15 above but in super-structure including necessary cutting and moulding of brick work as required and also including honey combed brick work in thickness of wall one brick thick. 1:6 1 cement and 6 coarse sand mortar					
	BOUNDARY WALL	PWD 303+309+31 0	1.49	CUM		
13	External Plastering 12 mm thick plaster with cement mortar in proportion of 1:6cement & fine sand of along for external walls	-	18.72	SQM		
18	Finishing walls with Acrylic smmoth exterior paint of required shade: New work (Two or more coats applied @ 1.67 ltr/10 sqm) over and including priming coat of exterior primer applied @ 2.20kg/ 10 sqm		18.72	SQM		
19	Providing & applying Birla putty of Av. 1. mm thickness over plastered surface to prepare the surface even & smooth complete		18.72	SQM		
21	Exterior landscape work & Lighting provision on Boundary wall as per direction & drawing of engineer- in charge.	L.S	1.00	Nos.		
22	Ms work in boundary wall as per direction of engineer- in charge	L.S	1.00	Nos.		
	COST 3 meter boundary wall (single panel)					
	Boundary wall total length 165.60 Meter		PANEL			
	TOTAL COST					